

多种口径滑膛枪头可以与博克水枪水幕器连接使用，如表所示

Choice of Solid Bore Tips to be Mounted on your COMBIPOK					
代码	枪头口径	输入工作压	直流流量	雾流流量	组合流量
Code	Tip Size	Inlet Pressure (psi)	Solid Bore Flow (gpm)	Fog Flow (gpm)	Combination Flow (gpm)
14232	3/8"	50	31	60	91
		75	37	80	117
		100	43	100	143
1566	1/2"	50	54	60	114
		75	65	80	145
		100	75	100	175
14233	5/8"	50	83	60	143
		75	102	80	182
		100	117	100	217
1704	3/4"	50	113	60	173
		75	146	80	226
		100	168	100	268
14234	7/8"	50	162	60	227
		75	198	80	278
		100	228	100	328
1537	15/16"	50	186	60	246
		75	227	80	307
		100	262	100	362
1536	1.0"	50	211	60	271
		75	258	80	338
		100	298	100	398
8947	1 1/4"	50	329	60	389
		75	403	80	483
		100	465	100	565
8278	1 3/8"	50	398	60	458
		75	487	80	567
		100	563	100	663

Note: Other configurations available, dual, triple and quad stacked tips.

For more information, visit us on the Web at www.pokfire.com for some video clips.

获取更多信息，请浏览博克网站 www.pokfire.com 并且有录像短片提供。

名 称	代 码
博克水枪水幕器	14196