



**TECHNICAL SERVICE PART LIST
 3 FOOT PIERCING NOZZLE #8955**

⚠ WARNING ⚠

- ❶ Uses Parker-O-Lube on All O-Rings.
- ❷ Uses Permabond LM 113 or Loctite 222 on All Screws.

TECHNICAL SERVICE PARTS LIST

3 Foot piercing nozzle #8955

3 foot piercing nozzle				
Number	Stock ID	Description	Quantity	Price Unit.
1	800	Replacement tip	1	
2	801	Replacement for head	1	
3	R22	O-ring R22	1	
4	8955B	3ft piercing nozzle body	1	
5	11698	Body 1.0" WW w/o pistol grip	1	
6	B2-10	Ball valve in aluminium	1	
7	10248	Handle in polyurethane	1	
8	2405	Trunnion nut in stainless	2	
9	R12	O-ring R12	2	
10	R7	O-ring R7	2	
11	20.5x12.5x2	White nylon spacer	2	
12	2602	Trunnion screw in stainless	2	
13	BBØ4	Ball bearing Ø4	37	
14	3742	Gasket for 1.5" NST	1	
15	1675	Swivel coupling 1.5" F NST	1	
16	10741	1.0" Outlet, 1.5" NST	1	
17	2385	1.0" waterway ball valve seat	1	
18	54x3	O-ring 54x3	1	
19	STHCFM8x6	Socket hex flat set screw M8x6	1	
20	48x30x4	Gasket 48x30x4	1	
21	R31	O-ring R31	1	
22	BBØ4	Ball bearing Ø4	44	
23	1665	Inlet swivel coupling	1	
24	BBØ4	Ball bearing Ø4	37	
25	1675	Swivel coupling 1.5" F NST	1	
26	3742	Gasket for 1.5" NST	1	
27	STHCFM6x6	Socket hex flat set screw M6x6	1	
28	STHCPM5x5	Socket hex cone set screw M5x5	1	
29	STHCFM6x6	Socket hex flat set screw M6x6	1	