



**TECHNICAL SERVICE PART LIST
 5 FOOT PIERCING NOZZLE #2306**

⚠ WARNING ⚠

- ❶ Uses Parker-O-Lube on All O-Rings.
- ❷ Uses Permabond LM 113 or Loctite 222 on All Screws.

TECHNICAL SERVICE PARTS LIST

5 Foot piercing nozzle #2306

5 foot piercing nozzle				
Number	Stock ID	Description	Quantity	Price Unit.
1	800	Replacement tip	1	
2	801	Replacement for head	1	
3	R22	O-ring R22	1	
4	2306B	5ft piercing nozzle body	1	
5	11698	Body 1.0" WW w/o pistol grip	1	
6	10248	Handle in polyurethane	1	
7	2405	Trunnion nut in stainless	2	
8	R12	O-ring R12	2	
9	R7	O-ring R7	2	
10	20.5x12.5x2	White nylon spacer	2	
11	2602	Trunnion screw in stainless	2	
12	BBØ4	Ball bearing Ø4	37	
13	3742	Gasket for 1.5" NST	1	
14	1675	Swivel coupling 1.5" F NST	1	
15	10741	1.0" Outlet, 1.5" NST	1	
16	2385	1.0" waterway ball valve seat	1	
17	54x3	O-ring 54x3	1	
18	B2-10	Ball valve in aluminium	1	
19	48x30x4	Gasket 48x30x4	1	
20	R31	O-ring R31	1	
21	BBØ4	Ball bearing Ø4	44	
22	1665	Inlet swivel coupling	1	
23	BBØ4	Ball bearing Ø4	37	
24	1675	Swivel coupling 1.5" F NST	1	
25	3742	Gasket for 1.5" NST	1	
26	STHCFM6x6	Socket hex flat set screw M6x6	1	
27	STHCPM5x5	Socket hex cone set screw M5x5	1	
28	STHCFM8x6	Socket hex flat set screw M8x6	1	
29	STHCFM6x6	Socket hex flat set screw M6x6	1	