



SLIDE-O-MATIC 600

AUTOMATIC GALLONAGE/DUAL PRESSURE

Nozzles in Hardcoat Anodized Aluminum and PTFE

The SLIDE-O-MATIC offers a durable, lightweight dual pressure, 50 and 100 PSI automatic gallonage nozzle with the features that you are looking for and especially for CAF systems. Machined out of high-grade aluminum alloy with the trademarked NITUFF™ finish that gives 50 microns of PTFE impregnated anodized unlike the 20 microns of standard anodized.

Features a wide flow range from 15 to 250 GPM at either standard or low pressure. Easy to operate ring for standard (100 PSI) or low pressure (50 PSI) selection. Newly engineered design totally encapsulates the stainless steel piston valve and handle flow position stops from the environment. Neither dirt, sand, frozen water or other debris on the outside or inside of the nozzle will prevent you from switching between the 6 flow settings using the handle.

Our new technology contains a redundant system for each flow selection resulting in greater user safety. With a quick half turn of the bumper guard the nozzle will go from full fog to straight stream and flush, all without having to shut down.

The SLIDE-O-MATIC also offers customizing with color-coded bumper, pistol grip and type of teeth. Comes standard with a black bumper guard and pistol grip.



Code	Description	W	H	L	Weight	FLOW	
						GPM	LPM
25126	SLIDE-O-MATIC 600 nozzle with dual pressure ring 1.5" inlet	3.5"	11.0"	13.0"	6.1 lb	15-250	60-750