



# SHUTOFFS & PLAYPIPE

Hardcoat Anodized Aluminum and PTFE

Machined out of high-grade aluminum alloy with the trademarked NITUFF™ finish that gives 50 microns of PTFE impregnated anodized unlike the 20 microns of standard anodized, full waterway and designed to reduce friction loss and turbulence. Available in 1.0", 1.5" and 2.5" double ball bearing swivel inlet and a standard machine ball is also coated using the NITUFF™ process, which provides years of smooth action with minimal wear.

Customize your shut-off with color-coded pistol grip, shutoff handle or ball valve in Polyamide or in stainless steel.

### Color coded system



### Shutoffs without Pistol Grip

Code	Inlet	Outlet	Ø waterway (mm / inch)	W	H	L	Weight
9981	Female 1.0"	Male 1.0"	25 / 1.0"	4.5"	6.0"	5.5"	2.2 lb
9983	Female 1.5"	Male 1.5"	25 / 1.0"	4.5"	6.0"	5.5"	2.4 lb
9985	Female 1.5"	Male 1.5"	35 / 1 3/8"	5.0"	6.0"	5.0"	2.8 lb
9986	Female 2.5"	Male 1.5" or 2.5"	35 / 1 3/8"	5.0"	6.0"	9.5"	4.1 lb
9989	Female 2.5"	Male 2.5"	52 / 2.0"	5.0"	6.0"	7.5"	4.7 lb

### Single Pistol Grip Shutoffs

Code	Inlet	Outlet	Ø waterway (mm / inch)	W	H	L	Weight
13341	F 3/4" or 1.0"	Male 3/4" or 1.0"	15 / 3/4"	4.0"	9.0"	6.0"	1.8 lb
9982	Female 1.0"	Male 1.0"	25 / 1.0"	4.5"	10.0"	5.5"	2.9 lb
9984	Female 1.5"	Male 1.5"	25 / 1.0"	4.5"	10.0"	5.5"	2.9 lb
9990	Female 1.5"	Male 1.5"	35 / 1 3/8"	5.0"	10.0"	5.2"	3.5 lb
9987	Female 2.5"	Male 1.5" or 2.5"	35 / 1 3/8"	5.0"	10.0"	8.0"	4.8 lb

### Twin Pistol Grip Shutoff

Code	Inlet	Outlet	Ø waterway (mm / inch)	H	W	L	Weight
9988	Female 2.5"	Male 1.5" or 2.5"	35 / 1 3/8"	5.0"	14.5"	10.5"	6.7 lb

SHUTOFF without PISTOL GRIP



SHUTOFF with PISTOL GRIP 13341



SHUTOFF with PISTOL GRIP 9982-9984-9990



SHUTOFF with PISTOL GRIP 9987



PLAYPIPE with TWIN PISTOL GRIP

