



# WILDLAND TIPS SINGLE and DUAL GALLONAGE

The Wildland tips offer a durable, lightweight constant or dual gallonage following the NFES standard. Machined out of high-grade aluminum alloy with the trademarked NITUFF™ finish that gives 50 microns of PTFE impregnated anodized or the 20 microns standard anodized process. The twist shutoff feature is made of durable material, which provides years of smooth action with minimal wear.

The ROBATFLAM and WILDLAND single grip offer flow ranges from 5, 10, 15, 20, 25, 30, 32, 37, 40 or 60 @ 100 PSI in a ¾" or 1.0" inlet. The dual gallonage offers a choice of 10-24 GPM or 20-60 GPM by a simple twist of the tip in ¾", 1.0" and 1.5" inlet. Large bumper guard allows for easy change from straight stream to narrow fog to wide-angle fog to flush without having to shutdown. Customizing with color-coded bumper on the dual gallonage and BATFLAM 12600 and 13042 only. Comes standard with a black bumper guard.

*\*Available color coded Bumper Guard 150 series NFES (National Fire Equipment System)*



DUAL GALLONAGE 10-24 GPM without Bumper Guard



DUAL GALLONAGE 10-24 GPM with Bumper Guard



DUAL GALLONAGE 20-60 GPM with Bumper Guard



BATFLAM with spinning teeth



BATFLAM without spinning teeth



BATFLAM 3182 with molded teeth



BATFLAM 3181 with molded teeth

Code	Description	W	L	Weight
17748	Wildland Tip 10-24 GPM, 1.0" F NST Inlet - NFES #1081	2.0"	3.5"	0.56 lb
17751	Wildland Tip 10-24 GPM, ¾" GHT Inlet	2.0"	3.5"	0.56 lb
17497	Wildland Tip 10-24 GPM, 1.0" NPSH Inlet - NFES #1081	2.0"	3.5"	0.56 lb
*18404	Wildland Tip 10-24 GPM, ¾" GHT Inlet, with bumper guard	3.7"	3.5"	0.80 lb
*17991	Wildland Tip 10-24 GPM, ¾" Inlet, with bumper guard specify thread	3.7"	3.5"	0.80 lb
*18403	Wildland Tip 10-24 GPM, 1.0" F NST Inlet, with bumper guard	3.7"	4.5"	0.80 lb
*17506	Wildland Tip 20-60 GPM, 1.5" F NST Inlet, with bumper guard NFES #1082	3.0"	4.5"	0.92 lb
*17754	Wildland Tip 20-60 GPM, 1.5" F NPSH Inlet, with bumper guard NFES #1082	3.0"	4.5"	0.92 lb
*11171	BATFLAM Tip without spinning teeth 60 GPM, with bumper guard 1.0" or 1.5" inlet	3.0"	4.0"	0.86 lb
*13042	BATFLAM Tip with spinning teeth 20 or 40 GPM, with bumper guard ¾" GHT inlet	3.0"	4.0"	0.88 lb
*13043	BATFLAM Tip with spinning teeth 30 or 40 GPM, with bumper guard 1.0" or 1.5" inlet	3.0"	4.0"	0.88 lb
*12600	BATFLAM Tip without spinning teeth 30 or 40 GPM, with bumper guard 1.0" or 1.5" inlet. Specify GPM	3.0"	4.0"	0.88 lb
3182	BATFLAM Tip with molded teeth in aluminum with bumper guard 5-10-15-20-25-30-32 or 37 GPM, 1.0" inlet, specify GPM	2.0"	4.7"	0.92 lb
3181	BATFLAM Tip with molded teeth in brass with bumper guard 5-10-15-20-25-30-32 or 37 GPM, ¾", 1.0", or 1.5" inlet, specify GPM	2.0"	3.7"	1.60 lb