



# STREAM SHAPERS

Hardcoat Anodized Aluminum with PTFE

Machined out of high-grade aluminum alloy with the trademarked NITUFF™ finish that gives 50 microns of Teflon impregnated anodized unlike the 20 microns of standard anodized, designed to reduce friction loss and turbulence. Depending on the flow, a gain from 3 to 10 meters/3 to 30 feet can be obtained. All sizes come with a double ball bearing swivel for ease in connection and use. Other styles available for British Instantaneous, Storz, and special threads. Please call for details.



STREAM SHAPER 1.5" x 8.5" Long



STREAM SHAPER 2.5" x 4.5" Long



STREAM SHAPER 2.5" x 13.0" Long



## Stream Shapers

Inlet	Outlet	Lenght (mm / Inch)	Code
Female 1.5"	Male 1.5"	215 / 8.5"	2318
Female 2.5"	Male 2.5"	115 / 4.5"	1396
Female 2.5"	Male 2.5"	330 / 13"	2319

CONCENTRIC 1.5"x1.0"



## Concentric Adapters

Description	H (mm)	Code
Female 1.5" , Male 1.0"	110	1592
Female 2.5" , Male 1.5"	145	3452
Female 2.5" , Male 2.0"	160	8285

CONCENTRIC 2.5"x1.5"



## Quad Stacked Tips

Description	Inlet	Code
Quad 1 1/2" x 1 1/4" x 1 1/8" x 1.0" (38 x 32 x 28 x 25 mm)	2.5"	8283
Quad 2" x 1 3/4" x 1 1/2" x 1 3/8" (50 x 45 x 38 x 35 mm)	2.5"	8282

QUAD STACKED TIPS



Quad Stacked Tips 2.25" X 17.0" - 3.38 lb