



POK CLEAN - Solid cleaning agent

- ~ A cleaning agent with a detergent action for washing and degreasing the surfaces of roads, equipment, etc.
- ~ Used exclusively with POK FOAM nozzles or proportioners with Quick Stik Technology.
- ~ Its shelf life is 5 years (if stored in the original intact packing). It should be stored at temperatures from 0 °F (-18 °C) to 95 °F (+35 °C).
- ~ The solid agent is not harmful to health and is easily biodegradable. It does not contain fluorinated substances.
- ~ Remove the packing and sleeve before use.
- ~ Manufacturer: Buckeye Fire Equipment Company.
- ~ Weight: 1.21 ± .05 lbs./550 ± 25 grams
- ~ Yield of one cartridge (depends on water temperature) ca. 396 gallons/ca. 1500 liters



POK CLASS A - Solid foaming agent for Suppressing Class A Fires

- ~ An environmentally safe foaming agent for extinguishing wildland fires, high piled ordinary combustibles, silos or bunkers of bulk materials, etc.
- ~ Used exclusively with POK FOAM nozzles or proportioners with Quick Stik Technology.
- ~ Its shelf life is 5 years (if stored in the original intact packing). It should be stored at temperatures from 0 °F (-18 °C) to 95 °F (+35 °C).
- ~ The wetting agent is not harmful to health and is easily biodegradable. It does not contain fluorinated substances.
- ~ Remove the packing and sleeve before use.
- ~ Manufactured in solid stik form using Buckeye's USDA Forest Service Approved Class A Liquid Concentrate.
- ~ Manufacturer: Buckeye Fire Equipment Company.
- ~ Weight: 1.26 ± .05 lbs./570 ± 25 grams
- ~ Yield of one cartridge (depends on water temperature) ca. 660 gallons/ca. 2500 liters



POK CLASS A&B - Solid foaming agent for Suppressing Class A&B Fires

- ~ A foaming agent containing foam and film-forming components (AFFF) for extinguishing flammable/combustible liquid and solid fires, etc.
- ~ It is used exclusively with POK FOAM nozzles or proportioners with Quick Stik Technology.
- ~ Its shelf life is 5 years (if stored in the original intact packing). It should be stored at temperatures from 0 °F (-18 °C) to 95 °F (+35 °C).
- ~ The extinguishing agent is not harmful to health and is easily biodegradable. It contains fluorinated substances.
- ~ Remove the packing and sleeve before use.
- ~ Manufactured in solid stik form using Buckeye's U.L. Listed Ingredients.
- ~ Manufacturer: Buckeye Fire Equipment Company.
- ~ Weight: 1.21 ± .05 lbs./ 550 grams ± 25 grams
- ~ Yield of one cartridge (depends on water temperature) ca. 396 gallons/ca. 1500 liters

